



CENTRAL UNIVERSITY OF HARYANA

(Established vide Act No. 25 (2009) of Parliament)

Jant-Pali, Mahendergarh-123029

NOTICE INVITING QUOTATION NO. 38/2025

Name of Work: Name of Work: Repair of damaged false ceiling (including dismantling, replacement & painting) in Academic Block-1 and Academic Block-4.

Sealed percentage rate quotations are invited on behalf of Central University of Haryana, Mahendergarh from registered government contractor. The quotation should reach the office of the Executive Engineer, Room No.-217, Administrative Building, CUH on or before 21/08/2025 upto 01:00 PM. The quotation shall be opened on the same day i.e. 21/08/2025 at 03:00 PM. The bidders may attend the said meeting on 16/05/2025.

The terms & conditions for the same are given below:

1. The BOQ is attached as **Annexure-'I'**.
2. The work will be carried out as per CPWD specifications and as per the satisfaction of the Engineer-in-Charge.
3. The agency/firm must deposit EMD of Rs. 4,225/- (Rupees Four thousand two hundred twenty five only) in the form of NEFT/RTGS in favour of Central University of Haryana's Account No. 7824000100045526 IFSC Code: PUNB0782400 (Punjab National Bank, Jant-Pali, Mahendergarh).
4. The agency must submit the details of EMD submitted to CUH i.e. UTR details etc. along with bank account details of the agency/firm for the purpose of release of EMD of unsuccessful bidders.
5. GST registration certificate of the agency is required to be enclosed along with quotation.
6. Certificate of registration of the contractor/agency is required to be enclosed along with quotation.
7. Validity of the quotations will be 60 days from the date of opening.
8. The rate includes all taxes like GST, and other taxes and carriage of the material etc.
9. Time of completion of work will be 30 days.
10. No advance payment will be made.
11. Conditional quotations will not be considered.
12. The agency should inspect the site before quoting the rate.
13. The quantity of items in BOQ is tentative which may change depending upon site conditions.
14. The agency should provide proper safety tools to its workers. The CUH will not be responsible for any accident.
15. Time is the main essence of the contract. Hence, an appropriate penalty upto 10% maximum can be imposed on the agency for delayed completion of work.
16. No labor below the age of 18 years be employed on site.
17. All T&P required will be arranged by the contractor.
18. The agency/Contractor shall make its own arrangement of electricity, if CUH provide electricity for above said work, CUH will charge cost for the same.
19. Security deposit @5% and necessary recoveries i.e. GST, Labour Cess and Income Tax etc. will be recovered from the bills of the contractor.

Kumar G. 2
Executive Engineer
14/08/2025

Annexure-'I'

Name of Work: Repair of damaged false ceiling (including dismantling, replacement & painting) in Academic Block-1 and Academic Block-4.

Sr. No.	Description of item	Qty	Unit	Rate	Amount
1	Dismantling aluminium/ Gypsum partitions, doors, windows, fixed glazing and false ceiling including disposal of unserviceable material and stacking of serviceable material with in 50 meters lead as directed by Engineer-in-charge	100.00	Sqm.	56.35	5,635/-
2	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter	100.00	Sqm.	1355.80	1,35,580/-

12

Sr. No.	Description of item	Qty	Unit	Rate	Amount
	channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with : 12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095- (Part I) :2011 (Board with BIS certification marks)				
3	Providing and fixing mineral fibre false ceiling tiles at all heights of size 595X595mm of approved texture, design and pattern. The tiles should have Humidity Resistance (RH) of 99%, Light Reflectance ? 85%, Thermal Conductivity k = 0.052 - 0.057 w/m K, Fire Performance as per (BS 476 pt - 6 & 7) in true horizontal level suspended on interlocking T-Grid of hot dipped all round galvanized iron section of 0.33 mm thick (galvanized @120 gsm) comprising of main T runners of 15x32 mm of length 3000 mm, cross T of size 15x32mm of length 1200 mm and secondary intermediate cross T of size 15x32 mm of length 600 mm to form grid module of size 600x600 mm suspended from ceiling using galvanized mild steel item (galvanised@80gsm) 50 mm long 8mm outer diameter M-6 dash fasteners, 6 mm diameter fully threaded hanger rod up to 1000 mm length and L-shape level adjuster of size 85x25x2 mm, spaced at 1200 mm centre to centre along main 'T'. The system should rest on periphery walls /partitions with the help of GI perimeter wall angle of size 24x24X3000 mm made of 0.40 mm thick sheet, to be fixed to the wall with help of plastic rawl plug at 450 mm centre to centre & 40 mm long dry wall S.S. screws. The exposed bottom portion of all T-sections used in false ceiling support system shall be pre-painted with polyester baked paint, for all heights. The work shall be carried out as per specifications, drawings and as per directions of the engineer-in-charge. With 16 mm thick beveled tegular mineral fibre false ceiling tile (NRC 0.55 to 0.6	30.00	Sqm.	2333.60	70,008/-
	Total				2,11,223/-
	% Above/Below				
	Quoted amount in Rupees:				

Signature & stamp of Contractor/Agency